



Model: 50

Watts: 500

Heat Stages: 4



Output Voltages

Switch

Position AC/High

1 1.8

2 2.1

3 2.4

4 2.7

1. Choose one of three secondary circuits: AB/Low, BC/Medium, AC/High
 - It is recommended first using AB/Low—switch position '1'.
2. Fasten the pencil cord to either terminal of the selected circuit and the ground cord to the other terminal.
3. Clamp the work piece with the ground clamp and begin marking as with a pencil.
 - To make a grounding plate for high production work, clamp or bolt ground cord to a metal plate and place work piece directly onto plate.
4. Turn selector switch (and/or change secondary circuit) to gradually increase heat until desired result is achieved for the application.
 - For best performance keep points sharpened by rotating against a grinding wheel.

To see our complete line of equipment:

- *Etching*
- *Soldering*
- *Demagnetizing*

Visit us at www.lumaelectricco.com

Parts checklist:

- (1)#9207 Pencil Cord (42")
- (1)#8 Ground Cord (36")
- (1)#9230 Copper Point
- (1)#9232 1/8" Tungsten point
- (1)#9234 3/16" Tungsten point
- (1)#9228 Fine Tungsten point
- (2) 5/16" Attachment Knob
- (1) Switch Knob

Luma Electric Co.

3419 Silica Road

Sylvania, Ohio 43560

PH: 419-843-7842

FAX: 419-843-7984

email: info@lumaelectric.com

website: www.lumaelectricco.com